

COMPACT AND PORTABLE KVM OVER USB DEVICE



The simplest way to manage local servers and headless computers, with KVM over USB.

Control any target computer that has VGA, DVI, or HDMI[™] output. There's nothing to install on the target, meaning you can capture bootup sequences and proprietary OSes.

Capture up to 1080p video with ultra-smooth 60 frames per second.

Small and portable, but also tough. This USB-powered KVM has an all-metal enclosure designed for daily use.



Technical specifications

Interface	Host:	USB 3.0
	Target:	HDMI, DVI, or VGA video. USB mouse and keyboard
Input resolutions	Up to 1900×1200, including 1080p VESA modes: 720×400, 640×480, 800×600, 1024×768, 1152×864, 1152×900, 1280×960, 1280×1024, 1920×1080, 1900×1200	
Dimensions	3.54" × 2.36" × 0.91" (90 mm × 60 mm × 23 mm)	
Device connectors	One DVI female connector (for KVM cable) One USB B-type connector	
KVM cable connectors	DVI male (connect to KVM2USB 3.0) DVI female (connect another male to male cable to connect to target) USB 2.0 (connect to target)	
LEDs	One LED to indicate the status of the KVM2USB 3.0 (power, readiness, and operation in progress)	
OS support	Windows 10, Linux Ubuntu 16.04 or higher	
Country of origin	Made in China	

www.epiphan.com

Email: info@epiphan.com North America +1-877-599-6581 International +1-613-599-6581

[™] and © 2019 Epiphan Systems Inc.

Epiphan, Epiphan Video, Epiphan Systems, its products names and logos are tradenames or trademarks of Epiphan Systems Inc. All other company, interface and product names and logos are trademarks or registered trademarks of their respective owners in certain countries. Product descriptions and specifications regarding the products in this document are subject to change without notice.